## N4 THERMOPLASTIC EMERGENCY UNIT



# **Product Features:**

- Two round adjustable heads
- High performance reflector/lens assembly
- Redesigned snap-in assembly
- Choice of battery capacity and lamp wattage
- White or Black finish
- Available with remote load capacity








Designed to meet the user's demands, the N4 series of emergency lighting units embraces the feedback we received from our customers through the years. A PAR 36 size round reflector combined with a spread lens deliver a beam pattern optimized to illuminate the path of egress. The different lamp configurations can increase the spacing between fixtures reducing wiring, installation, and maintenance costs. A redesigned snap-in construction improves the ease of installation.


# **N4** Thermoplastic Emergency Lighting Unit

|                        | Catalog # | Finishes | Lamps                     | Remote Capability                                |
|------------------------|-----------|----------|---------------------------|--|
| Standard Units         | N4WH      | White    | Two 6V 5W T5 Wedge Base   |  |
| Standard Units         | N4BL      | Black    | IWO 6V 3VV 13 Wedge Base  |  |
|                        | 1111111   | +        |                           | <del>                                     </del> |
| High Performance Units | N4WHHO7   | White    | Two 6V 7.2W T5 Wedge Base |  |
|                        | N4BLHO7   | Black    |                           |  |
|                        | N4WHHO9   | White    | Two 6V 9W T5 Wedge Base   |  |
|                        | N4BLHO9   | Black    |                           |  |
|                        | N4WHHO10  | White    | Two 6V 10W T5 Wedge Base  |  |
|                        | N4BLHO10  | Black    |                           |  |
| Remote Capable Units   | N4WHHO    | White    | Two 6V 5.4W T5 Wedge Base | Up to 10.8W                                      |
|                        | N4BLHO    | Black    |                           |  |










#### Recommended Fixture Spacing

| 3 Feet Wide Path of Egress |             |                  |  |  |  |
|----------------------------|-------------|------------------|--|--|--|
| Lamp                       | Spacing (X) | Ave Illumination |  |  |  |
| 6V 5.4W                    | 18.5 ft.    | 1.03 FC          |  |  |  |
| 6V 7.2W                    | 22 ft.      | 1.04 FC          |  |  |  |
| 6V 9W                      | 26 ft.      | 1.03 FC          |  |  |  |

### Fixture spacing calculation:

Room reflectances 80/50/20 ceiling, walls, and floor respectively Fixtures mounted 7' from the floor for 5.4W and 7.2W lamps, and 7.5' from floor for 9W lamps

Values represent an approximation and are based on an open environment Juno Lighting Group takes no responsibility for local requirements or specific project variables. Information is provided only as an approximation of coverage/spacing.



1300 South Wolf Road • P.O. Box 5065 • Des Plaines, Illinois 60017-5065 PHONE (847) 827-9880 • FAX (847) 827-2925 • junolightinggroup.com

### Regional Offices & Warehouses:

Atlanta, Dallas, Los Angeles, Philadelphia, Toronto



NaviLite is a registered trademark of Juno Lighting, Inc. Products shown in this brochure are covered by U.S. and international patents and patents pending. Specifications subject to change without notice. © 2007 JUNO LIGHTING INC.



