



U5136-O-100S-55-FMG



Catalog Number	U5136-O-100S-55-FMG
Marketing Product Description	4 Terminal Ringless Plain Top 1-100 Ampere Main Breaker 1450 520GR Single Pedestal Direct Bury Florida Meter Group
UPC	784572507753
Length (IN)	10.25
Width (IN)	9.688
Height (IN)	80
Brand Name	Milbank
Type	Ringless Meter Socket
Special Features	One Single Pole 20 Ampere Breaker and One Double Pole 50 Ampere Breaker
Application	Mobile Home Power
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	10.25L x 9.688W x80H
Number Of Cutouts	3

Cutout Size	One 100 Ampere Main Breaker and One Single Pole 20 Ampere Breaker and One Double Pole 50 Ampere Breaker
--------------------	---

Cable Entry	Underground
Terminal	Double Mechanical
Insulation	Glass Polyester
Mounting	Pedestal
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	Horn Bypass
Number of Meter Positions	Single Power Head
Equipment Ground	Ground Bar
Hub Opening	Plain Top
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	1 - 3 AWG
Number Branch Circuits	1
Number Of Receptacles	2
Receptacle Configuration	One NEMA 14-50 and One NEMA 5-20 Ground Fault

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.