



MILBANK
ENERGY AT WORK

UAP6096-O



| | |
|--------------------------------------|---|
| Catalog Number | UAP6096-O |
| Marketing Product Description | Aluminum Painted Shell 14 Position Per Phase Bar 750 Kcmil |
| UPC | 784572759633 |
| Length (IN) | 16 |
| Width (IN) | 25.938 |
| Height (IN) | 51 |
| Weight (LB) | 115 |
| Brand Name | Milbank |
| Type | Hinge Cover |
| Special Features | 3300 Ampere; Three Phase Four Wire; Penta Bolt; 10,000 Short Circuit Current Rating |
| Application | Terminate Conductors |
| Standard | UL Listed |
| Number Of Outlet | 0 |
| Material | Aluminum |
| Size | 25.938 In x 16 In x 51 In |
| Color | ANSI 61 Gray |
| Insulation | Stand Off's |
| Construction | Welded |
| Cable Entry | No Knockouts |
| Mounting | Pad Mount or Wall Mount |

| | |
|--------------------|---|
| NEMA Rating | Type 3R |
| Hinge Type | Lift Off Hinges |
| Top | Plain Top |
| Door | Hinged Cover |
| Latch | Padlocking Handle with 3 Point Latch Assembly |
| Support | Body Stiffeners |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.