

MULTIPLE CONNECTORS

Combination Connectors




FEATURES

- Multiple combination connectors are made from aluminum and are tin-plated for low contact resistance.
- Suitable for use with both copper and aluminum conductors.
- Each connector contains a combination of 1/0-14 AWG and 6-14 AWG wire holes.
- Economical and compact due to innovative design and hole spacing.
- Dual rated for use with aluminum and copper cables.

RATINGS



CAT. NO.	FIG.
2024	1
2024M	2
2024MB	4
2030	1
2030M	2
2030B	3
2030MB	4
2036	1
2036M	2
2036MB	4
2042M	2
2042MB	4





NO. OF 4-14 AWG CIRCUITS	NO. OF 1/0-14 AWG CIRCUITS	MAIN LUG SIZE	MOUNTING BASE	LENGTH	HEIGHT	WIDTH	STD. CTN. QTY.
20	4	None	No	4.332	1.025	1.687	1
20	4	350-6	No	4.457	1.525	1.687	1
20	4	350-6	Yes	4.457	2.900	2.437	1
26	4	None	No	5.244	1.025	1.687	1
26	4	350-6	No	5.369	1.525	1.687	1
26	4	None	Yes	5.244	2.400	2.437	1
26	4	350-6	Yes	5.369	2.900	2.437	1
32	4	None	No	6.156	1.025	1.687	1
32	4	350-6	No	6.281	1.525	1.687	1
32	4	350-6	Yes	6.281	2.900	2.437	1
38	4	350-6	No	7.193	1.525	1.687	1
38	4	350-6	Yes	7.193	2.900	2.437	1