


# SWITCHES

## Indicator LightS & Emergency Stop Buttons



### FEATURES

- Terminals are tin-plated brass.
- Wire leads are 22 AWG, 4.4-4.8" long, 1/2" stripped.
- Mounting will snap-fit into 0.500-0.505" diameter hole in 0.020-0.100" thick panels.
- Dome style.



CAT. NO.	COLOR	LENS MATERIAL	VOLTAGE	BULB TYPE	BAG QTY.	STD. CTN. QTY.
<b>79900LW</b>	Red	Polycarbonate	28V	Incandescent	1	12
<b>79901LW</b>	Green	Polycarbonate	28V	Incandescent	1	12
<b>79902LW</b>	Amber	Polycarbonate	28V	Incandescent	1	12
<b>79910LW</b>	Red	Nylon	105-125VAC	Neon	1	12
<b>79911LW</b>	Green	Polycarbonate	105-125VAC	Neon	1	12
<b>79912LW</b>	Amber	Nylon	105-125VAC	Neon	1	12
<b>79920LW</b>	Red	Polycarbonate	208-250 VAC	Neon	1	12
<b>79921LW</b>	Green	Polycarbonate	208-250 VAC	Neon	1	12
<b>79922LW</b>	Amber	Polycarbonate	208-250 VAC	Neon	1	12

### EMERGENCY STOP BUTTON



CAT. NO.	NAED NO.	LENS COLOR	STD. CTN. QTY.
<b>ESB2-INC-R</b>	32132	Red	6
<b>ESB2-INOINC-R</b>	32136	Red	6