

EASY-TWIST™
Wire Connector
Combination Pails
WC & WWC SERIES



FEATURES

- Compact, easy to carry pail, also convenient for use on maintenance cart.
- 4-pack pail includes the most common Easy-Twist™ connectors.



RATINGS



UL 486C Listed Wire Connector.

TEMPERATURE RATING:
 105 °C (221 °F).

VOLTAGE:
 1,000V max. in fixtures and signs.

WIRE TYPE:
 For copper wire only.



Scan QR code for mobile access to wire combinations.

CAT.
NO.

ET-CP-1

ET-CP-2

ET-CP-3

ET-CP-11

ET-CP-12

ET-CP-13

ET-CP-14

ET-CP-15



PAIL CONTENTS	COLOR	WIRE RANGE	QTY. PER PAIL	STD. CTN. QTY.
WWC-T	Tan	22-8 AWG	70	12
WWC-Y	Yellow	18-10 AWG	80	
WWC-R	Red	18-8 AWG	45	
WWC-B	Blue	14-6 AWG	20	
WC-O	Orange	22-14 AWG	100	12
WC-Y	Yellow	22-10 AWG	75	
WC-R	Red	22-10 AWG	50	
WWC-T	Tan	22-8 AWG	70	
WC-O	Orange	22-14 AWG	100	12
WWC-T	Tan	22-8 AWG	70	
WWC-Y	Yellow	18-10 AWG	80	
WWC-R	Red	18-8 AWG	45	
WWC-T	Tan	22-8 AWG	40	16
WWC-Y	Yellow	18-10 AWG	50	
WWC-R	Red	18-8 AWG	30	
WWC-B	Blue	14-6 AWG	10	
WC-O	Orange	22-14 AWG	65	16
WC-Y	Yellow	22-10 AWG	45	
WC-R	Red	22-10 AWG	30	
WWC-T	Tan	22-8 AWG	40	
WC-O	Orange	22-14 AWG	60	16
WWC-T	Tan	22-8 AWG	45	
WWC-Y	Yellow	18-10 AWG	50	
WWC-R	Red	18-8 AWG	30	
WC-O	Orange	22-14 AWG	65	16
WC-Y	Yellow	22-10 AWG	45	
WC-R	Red	22-10 AWG	30	
WC-B	Blue	22-14 AWG	100	
WC-G	Gray	22-14 AWG	120	16
WC-B	Blue	22-14 AWG	100	
WC-O	Orange	22-14 AWG	65	
WC-Y	Yellow	22-10 AWG	45	