


REMOVABLE CAP  
TO TIGHTEN SCREW  
(REPLACE WHEN COMPLETE)

REMOVABLE CAP  
FOR DUAL ENTRY  
(INSERT IN OTHER SIDE)

3/8 INTERNAL  
HEX PRESSURE SCREW



WIRE ENTRY PORT  
WIRE RANGE: 750KCMIL - 250  
PRE-FILLED W/ OXIDE INHIBITOR



IPLDS750-10 SHOWN

NSI PART NUMBER	NO. OF PORTS	LENGTH
IPLDS750-4	4	3.55
IPLDS750-6	6	4.95
IPLDS750-8	8	6.38
IPLDS750-10	10	7.80
IPLDS750-12	12	9.23
IPLDS750-14	14	10.66

CONTACT NSi FOR SALES @ 800.321.5847

		<b>POLARIS</b> SALES CO. INC
<small>PROPRIETARY AND CONFIDENTIAL</small>		<small>11625 PROSPEROUS DRIVE ODESSA, FL 33556</small>
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.</small>		<b>TITLE:</b> INSULATED STACKED DUAL ENTRY (BOTTOM ROW) 750 CONNECTOR
<small>NAME</small> S.PARRY	<small>DATE</small> 06/2012	<b>DWG. NO.</b> IPLDS750-
<b>MATERIAL:</b> N/A		<b>SCALE:</b> N/A
		<b>SHEET:</b> 1 OF 1

**NOTES:**

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.