



REMOVABLE CAP TO TIGHTEN SCREW (REPLACE WHEN COMPLETE)

INSULATED MOUNTING PORT ON EACH END FOR 1/4 BOLT

WIRE ENTRY POINT
WIRE RANGE: 1/0 - #14 AWG
PRE-FILLED W/ OXIDE INHIBITOR

3/16 INTERNAL HEX PRESSURE SCREWS

CONTACT NSI FOR SALES @ 800.321.5847

IPLM1/0-4 SHOWN

| PART NUMBER | NO. OF PORTS | LENGTH |
|-------------|--------------|--------|
| IPLM1/0-3 | 3 | 3.46 |
| IPLM1/0-4 | 4 | 4.11 |
| IPLM1/0-5 | 5 | 4.76 |
| IPLM1/0-6 | 6 | 5.41 |
| IPLM1/0-7 | 7 | 5.81 |
| IPLM1/0-8 | 8 | 6.71 |
| IPLM1/0-10 | 10 | 8.01 |
| IPLM1/0-12 | 12 | 9.06 |

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.

| | | POLARIS SALES CO. INC | | | | | |
|---|---------|--|----------------------|---------|---------|-----------------------------|--|
| PROPRIETARY AND CONFIDENTIAL | | 11625 PROSPEROUS DRIVE ODESSA, FL 33556 | | | | | |
| THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED. | | TITLE: INSULATED MOUNTED 1/0 CONNECTOR | | | | | |
| <table border="1"> <tr> <th>NAME</th> <th>DATE</th> </tr> <tr> <td>S.PARRY</td> <td>06/2012</td> </tr> </table> | | NAME | DATE | S.PARRY | 06/2012 | DWG. NO. IPLM1/0- | |
| NAME | DATE | | | | | | |
| S.PARRY | 06/2012 | | | | | | |
| MATERIAL: N/A | | SCALE: N/A | SHEET: 1 OF 1 | | | | |