

# TOOLS

## Hydraulic Compression Tools



### DIELESS HYDRAULIC CRIMPING TOOL



- Dieless indent style crimping head does not require interchangeable crimping dies.
- Flip-open Crimping head rotates 350 degrees to get into tight locations.
- Two-speed pump provides rapid crimping cycle time.
- Lightweight and strong fiberglass handles.
- Comes with a molded carrying case.
- Copper: 4AWG-1000kcmil (MCM).
- Aluminum: 6AWG-1000kcmil (MCM).
- UL and cUL Listed\*

CAT. NO.	DESCRIPTION	LENGTH (IN)	WEIGHT (LBS)	STD. CTN. QTY.
<b>N121D</b>	Dieless Hydraulic Crimping Tool	26	15	1

### 12 TON HYDRAULIC CRIMPING TOOL



- N1240 with 1.65 in (42mm) opening.
- Accepts KC12, KA12 and KD12 crimping dies as well as industry "U" style dies.
- New head design results in lower weight and improved durability – tested to 50,000 crimp cycles.
- Two-speed pump to reduce cycle time.
- Ram automatically retracts when crimp cycle is complete.
- Crimping heads rotate 350 degrees.
- Smaller and lighter than most tools. Includes carrying case.
- N1240 - 8 AWG to 750 kcmil copper and aluminum color-coded lugs and splices.
- UL and cUL Listed\*

CAT. NO.	DESCRIPTION	CRIMPING FORCE (IN)	LENGTH (IN)	WEIGHT (LBS)	STD. CTN. QTY.
<b>N1240</b>	12 Ton hydraulic Crimping Tool, 1.65 in. opening.	24,000	21-1/2	12.2	1

### CROSS REFERENCE GUIDE

NSI	GREENLEE	BURNDY	THOMAS & BETTS	ILSCO	HUSKIE	PANDUIT	BLACKBURN	PENN-UNION
<b>N1240</b>	KC12, KD12, U-Style	U	15500 Series	ILD	HT41	CD-920	B, H	T

\*UL and cUL classified with Anderson®, Blackburn®, Burndy®, ILSCO®, Panduit®, Thomas & Betts®, Penn-Union®, Tyco® color coded connectors. The products listed above are registered trademarks of Anderson®, Blackburn®, Burndy®, ILSCO®, Panduit®, Thomas & Betts®, Penn-Union® and Tyco®.

