

MECHANICAL CONNECTORS

Aluminum Dual Rated Parallel Groove Clamps

PAA, PAE SERIES



FEATURES

- High strength aluminum extruded alloy fittings assembled with steel or anodized high strength aluminum flat washers for heavy duty service entrance or for use as heavy duty distribution armor rod clamps.
- Serrated grooves provide increased contact.
- Supplied pre-filled with oxide inhibitor.
- For galvanized steel hardware, add the suffix -SH to each part number.

RATINGS

TEMPERATURE RATING:

90 °C.

VOLTAGE:

600V max.



All dimensional data is listed in inches.

CAT. NO.	FIG. NO.
PAA4	1
PAA5	1
PAA6	1
PAA10	1
PAA12	1
PAA29	1
PAA339	1
PAA49	1
PAA129	1
PAE2121-9	2
PAE4141-9	2



MAIN		TAP		HEX/WRENCH SIZE	BOLT HEIGHT	WIDTH (W)	LENGTH (L)	STD. CTN. QTY.
ACSR	AL/CU	ACSR	AL/CU					
1/0-6	1/0 STR-6 SOL	1/0-6	1/0 STR-6 SOL	3/8	1.187	1.500	2.219	25
1/0-8	1/0 STR-8 SOL	1/0-8	1/0 STR-8 SOL	3/8	1.496	1.496	1.240	25
1/0-8	2/0 STR-8 SOL	1/0-8	2/0 STR-8 SOL	3/8	1.496	1.496	1.240	25
336.4-1/0	400-1/0 SOL	1/0-8	1/0 STR-8 SOL	3/8	2.000	1.750	2.469	12
4/0-2	4/0 STR-2 SOL	4/0-2	4/0 STR-2 SOL	1/2	2.000	2.000	2.250	12
2-6	2 STR-6 SOL	2-6	2 STR-6 SOL	5/16	1.094	1.375	1.813	25
1/0-6	1/0 STR-6 SOL	1/0-6	1/0 STR-6 SOL	3/8	1.250	1.500	1.563	25
1/0-6	1/0 STR-6 SOL	1/0-6	1/0 STR-6 SOL	3/8	2.219	1.500	1.187	25
4/0-2	4/0 STR-2 SOL	4/0-2	4/0 STR-20L	1/2	2.250	2.000	2.000	12
2/0-6	2/0 STR-6 SOL	2/0-6	2/0 STR-6 SOL	3/8	2.000	1.625	1.375	25
4/0-4	4/0 STR-2 SOL	4/0-4	4/0 STR-2 SOL	3/8	2.000	2.000	1.375	12

TYPICAL

