

APPLICATIONS

- Offices, meeting rooms
- Energy code timed override
- Exhaust fans
- Equipment room and storage spaces



FEATURES

- UL listed for LED Lamp Drivers of up to 1200 watts
- Programmable 5 minutes to 24 hours
- Flash warning and/or beeper warning
- 3 way & multi-way compatible
- 2 hour timing for Title 24, 4 hour timing for ASHRAE 90.1
- Input voltage 120/230/277 VAC
- SS403: No neutral required for easy retrofit
- SS423: Requires a neutral for new construction
- SS410: Multiple circuits with power packs and low voltage for class 2 wiring

SPECIFICATIONS

TIMING ACCURACY: Line Frequency

INPUT VOLTAGE:

SS403/SS423 – 120/230/277VAC 50/60 Hz

SS410 – 24VDC OR 24VAC 50/60 Hz

WIRE SIZE:

SS403/SS423 – #14AWG input/output - #16AWG

3-way (remote)

SS410 – #18AWG

OPERATING TEMPERATURE:

32 °F to 104 °F (0 °C to 40 °C)

WARRANTY:

5 Yrs.



SS400 SERIES DIGITAL AUTO-OFF IN-WALL TIMER

**PROGRAM
MABLE!**



RATINGS

SS403:

15A Resistive @ 120-277VAC
10A Ballast @ 120-277VAC
1200W LED Lamp Driver @
120-277VAC
8A Tungsten @ 120-277VAC
360VA Pilot Duty @ 120VAC
1/4HP @ 120VAC

SS410:

28VDC .5A Max. 24VAC 1A Max.

SS423:

15A Resistive @ 120-277VAC
13A Ballast @ 120-277VAC
1200W LED Lamp Driver @
120-277VAC
8A Tungsten @ 120VAC
720VA Pilot Duty @ 120-277VAC
1HP @ 120-277VAC