

## WP68LED

Large Wallpack LED

55 Watt fixture  
5589 lumens output  
4700K color  
120-277VAC input



PROJECT INFORMATION: \_\_\_\_\_

\_\_\_\_\_

JOB: \_\_\_\_\_

APPROVALS: \_\_\_\_\_

\_\_\_\_\_

### APPLICATIONS

- Commercial buildings
- Shopping centers
- Schools
- Both inside and outside parking structures and interstate tunnels where general lighting is required to maintain a safe environment

### CONSTRUCTION

- Die cast aluminum housing
- Prismatic lens
- UV resistant powder coat finish
- Quick mount installation

### OPERATING TEMPERATURE

- Minimum: -30 °C
- Maximum: 50 °C

### ELECTRICAL

- AC Input Range: 120-277VAC 50/60Hz
- Input Power: 55W
- Input Frequency: 50~60Hz
- Inrush Current: >10A/115VAC >20A/230VAC
- Power Factor: >0.9
- THD: <0.2
- Surge Protection: 4kV

### LEDs

- Lumens per Watt: 102
- Watts: 55W
- Color Temperature: 4700K
- Color Index: 70+



### AGENCY LISTINGS

- UL Listed: Yes
- cUL Listed: Yes
- RoHS Compliant: Yes
- Wet Locations: Suitable

### WARRANTY

5-year Limited.  
See website for details.  
[www.nsiindustries.com](http://www.nsiindustries.com)

### DIMENSIONS



### ORDERING INFO

CAT. NO.	SYSTEM WATTS	LUMEN OUTPUT	COLOR	MA	INPUT VOLTAGE	CRI	STARTING TEMP.	EQUIVALENT
WP68LED	55	5589	4700K	950	120-277VAC	70+	-30 °C	150W - 200W MH

### PHOTOMETRIC REPORTS

