

WP68LED

Large Wallpack LED

70.2 Watt fixture
4887 lumens output
4700K color
120-277VAC input



PROJECT INFORMATION: _____

JOB: _____

APPROVALS: _____

APPLICATIONS

- Commercial buildings
- Shopping centers
- Schools
- Both inside and outside parking structures and interstate tunnels where general lighting is required to maintain a safe environment

CONSTRUCTION

- Die cast aluminum housing
- Prismatic lens
- UV resistant powder coat finish
- Quick mount installation

LIFESPAN

- L70 Calculated: 76,000
- L70 Reported: >60,000

OPERATING TEMPERATURE

- Minimum: -30 °C
- Maximum: 50 °C

DRIVER INFORMATION

- Type: Constant Current
- Class 2: cUL1310
- RoHS Compliant: Yes
- IP Rating: IP65
- Efficiency: 82% Typical
- PFC: >0.9
- EMI: EN55015, EN61547
- FCC: Class B

ELECTRICAL

- AC Input Range: 120-277VAC
- Input Current: 0.65A @ 120VAC
0.28A @ 277VAC
- Input Power: 70.2W
- Input Frequency: 50~60Hz
- Inrush Current: >10A/115VAC
>20A/230VAC
- Power Factor: >0.9
- THD: <0.2
- Surge Protection: 4kV
- Dimmable Option: Yes

LEDs

- 20 Hi Power LEDs: 4887 lumens
- LED Drive Current: 950mA
- Lumens per Watt: 70
- Watts: 3.51W
- Color Temperature: 4700K
- Color Index: 70+



AGENCY LISTINGS

- UL Listed: Yes
- cUL Listed: Yes
- RoHS Compliant: Yes
- Wet Locations: Suitable

WARRANTY

5-year Limited.
See website for details.
www.nsiindustries.com

DIMENSIONS



ORDERING INFO

CAT. NO.	SYSTEM WATTS	LUMEN OUTPUT	COLOR	MA	INPUT VOLTAGE	CRI	STARTING TEMP.	EQUIVALENT
WP68LED	70.2	4887	4700K	950	120-277VAC	70+	-30 °C	150W - 200W MH

PHOTOMETRIC REPORTS

