

Type \_\_\_\_\_  
 Project \_\_\_\_\_  
 Catalog No. \_\_\_\_\_  
 Lamp/Wattage \_\_\_\_\_

## NUTP3 Series 24V RGB LED Tape Light (Color Changing)

Source: 2.5 Watts Per Foot

### PRODUCT DESCRIPTION

RGB LED Tape Light has the colors Red, Green, and Blue in every LED diode. Several colors of visual spectrum can be selected and programmed with a 120° viewing angle. A stationary color, automatic changing colors and brightness can be selected and changed at anytime with the press of a button. This flexible LED light source is a durable silicone encapsulated tape, cETLus Listed for Wet Location applications and IP65 rated.

### FEATURES

- Available in 16' roll, 12" section, and 6" section
- Separable every 12", easily disconnected and connected without soldering
- Field cuttable every 6" or 6 LEDs
- 120° Beam Angle
- Easy to install; pre-applied 3M™ tape or 15 acrylic mounting clips (included with roll)
- Primary Colors: Red, Green, and Blue
- ETL Listed for Wet Location and IP65 rated
- No soldering or additional wiring is required
- No flicker delay or warm up like compact fluorescent products
- No UV light or infrared wavelengths
- 3 Year Limited Warranty

### CONSTRUCTION

The silicone encapsulated tape can be cut every 6 LEDs at marked intervals. Cutting does not effect circuit (shrink wrap tube included for concealment). RGB Tape Light is also separable every 12", each connection has pre-installed shrink wrap around power connections to ensure wet location listing. Simply slice the clear shrink wrap at each electrical connection, and separate pieces. This eliminates soldering when using partial rolls. Each roll comes with 12" power line connector NARGB-710.

### MOUNTING

Each Tape Light roll comes with 15 clear acrylic clips and also comes with pre-applied 3M™ adhesive tape for simple installation. An optional aluminum channel is available.

### ELECTRICAL

**Power:** 24 Volt DC Input / 2.5 Watts Per Foot / 40 Watts Per Roll

**Light Source:** 12 RGB LEDs Per Foot / 192 LEDs Per Roll

**Operating Temperature:** -25°C ~ 60°C (-13°F ~ 140°F)

**Life Expectancy:** 50,000 Hours

**Maximum Run Length:** 28' (w/ NMT-96/24C2) or 40' (w/ NATL-5100)

### CONTROLLER

Each run requires a controller, which can be linked together for color synchronization. The controller can be controlled locally or with an optional hand held remote.

### LABELS AND LISTINGS

cETLus Listed for Wet Location<sup>1</sup> (not submersible)

IP65 Rated


California Energy Commission

3 Year Limited Warranty



<sup>1</sup> To maintain wet location when connecting 2 sections; add clear shrink wrap over mating pieces and shrink wrap per instructions. (2) Shrink wrap tubes are included with each roll and section.

### DIMENSIONS



### RGB CONTROLLER (REQUIRED)

**NARGB-760:** 24VDC / 360W RGB Controller

**NARGB-761:** Hand Held Remote for RGB Controller

### HARDWIRE DRIVERS

**NATL-530HW:** 24VDC / 30W Class II Hardwired LED Driver

**NATL-560HW:** 24VDC / 60W Class II Hardwired LED Driver

**NATL-5100:** 24VDC / 100W Class II Plug-In LED Driver (hardwirable)

**NMT-60/24C2:** 24VDC / 60W Class II Magnetic LED Driver

**NMT-96/24C2:** 24VDC / 96W Class II Magnetic LED Driver

### PLUG-IN DRIVERS

**NATL-524:** 24VDC / 24W Direct Plug-In LED Driver

**NATL-545:** 24VDC / 45W Direct Plug-In LED Driver

**NATL-5100:** 24VDC / 100W Class II Plug-In LED Driver

### DRIVER ACCESSORIES

**NALTL-10:** 24VDC / 10' Power Line Connector for NMT-60/C2 & NMT-96/C2

**NALTL-30:** 24VDC / 30' Power Line Connector for NMT-60/C2 & NMT-96/C2

**NRA-125/6:** 6" Extension Cord for NATL-530HW & NATL-560HW

**NRA-125/12:** 12" Extension Cord for NATL-530HW & NATL-560HW

**NRA-125/18:** 18" Extension Cord for NATL-530HW & NATL-560HW

**NRA-125/72:** 72" Extension Cord for NATL-530HW & NATL-560HW

**NRA-6035W/6:** 6' Cord and Plug for NATL-530HW & NATL-560HW

**NRA-6035W/10:** 10' Cord and Plug for NATL-530HW & NATL-560HW

**NUSP-JBox:** Junction Box required for hardwiring NATL-530HW, NATL-560HW, NATL-5100

### RGB TAPE LIGHT ACCESSORIES

**NATL-400:** Shrink Wrap Tube (Pack of 5)

**NATL-403:** End Cap

**NARGB-700:** "Y" Splitter Cable

**NARGB-701:** "X" Splitter Cable

**NARGB-7xx:** Interconnection Cable (available in 2", 6", 18", 36", 72")

**NARGB-710:** 12" Power Line Interconnector

**NATHR-680:** 4' Aluminum Channel

**NATHR-685:** Clear Acrylic Mounting Clips (Pack of 15)


Create a complete fixture / driver catalog number: Example: NUTP3-16LEDRGB / NARGB-760 / NMT-96/24C2 / NALTL-30

| RGB Tape Light - select one             | LED Drivers     |                | Driver Accessories                 |              | Optional Accessories |                   |               |
|---|-----------------|----------------|------------------------------------|--------------|----------------------|-------------------|---------------|
| <b>Tape Light Length</b>                | <b>Hardwire</b> | <b>Plug-In</b> | <b>Class II Driver Accessories</b> |              | <b>Connectors</b>    | <b>Power Feed</b> | <b>Others</b> |
| NUTP3-16LEDRGB = 16' Roll               | ²NATL-530HW     | NATL-524       | NALTL-10                           | NRA-6035W/6  | NARGB-702            | NARGB-710         | NATL-400      |
| NUTP3-LEDRGB/6 = 6" Section             | ²NATL-560HW     | NATL-545       | NALTL-30                           | NRA-6035W/10 | NARGB-706            |                   | NATL-403      |
| NUTP3-LEDRGB/12 = 12" Section           | ²NATL-5100      | NATL-5100      | NRA-125/6                          | NUSP-JBox    | NARGB-718            |                   | NARGB-700     |
| <b>RGB Controller &amp; Remote</b>      | NMT-60/24C2     |                | NRA-125/12                         |              | NARGB-736            |                   | NARGB-701     |
| NARGB-760 = RGB Controller (Required)   | NMT-96/24C2     |                | NRA-125/18                         |              | NARGB-772            |                   | NATHR-680     |
| NARGB-761 = Hand Held Remote (Optional) |                 |                | NRA-125/72                         |              |                      |                   | NATHR-685     |

<sup>2</sup> Requires NUSP-JBox


## 24V RGB TAPE LIGHT ACCESSORIES

### NARGB-710 - 12" Power Line Interconnector



The 12" power line interconnector cable connects a Tape Light run to a Driver.  
NARGB-710 is included with every Tape Light roll (16').


### NATL-403 - End Cap



A: Width: 1/2"  
B: Length: 3/8"


Used to cover open end of Tape Light.

### NARGB-702 - 2" Interconnection Cable NARGB-706 - 6" Interconnection Cable NARGB-718 - 18" Interconnection Cable NARGB-736 - 36" Interconnection Cable NARGB-772 - 72" Interconnection Cable




The interconnection cables allow for the linking of any two Tape Lights in any direction or extension of power line interconnectors. The arrow on the interconnection cable must always be facing upward to maintain polarity. Interconnection cables may be joined together for custom lengths.

### NATHR-685 - Mounting Clips (Pack of 15)



Used to mount tape light to surface, includes mounting screws.  
Pack of 15 are included with every Tape Light roll (16')


### NARGB-700 - "Y" Splitter Cable NARGB-701 - "X" Splitter Cable



Cable Lengths: 3"


Splits connection from one Tape Light or Driver into two or three separate Tape Lights.

### NATHR-680 - 4' Aluminum Channel



Used to mount tape light to various surfaces. Tape Light snaps into the channel.  
Field Cuttable. Recommended for most installations.


### NATL-400 - Shrink Wrap Tube (Pack of 5)



Used to seal connections made in the field. Necessary to maintain ETL Wet Listing.  
Pack of 2 are included with every Tape Light roll and section.


## 24V RGB TAPE LIGHT LED DRIVER ACCESSORIES

- NRA-125/6** - 6" Flexible Connector
- NRA-125/12** - 12" Flexible Connector
- NRA-125/18** - 18" Flexible Connector
- NRA-125/72** - 72" Flexible Connector




Used to extend length between NUSP-JBox and NATL-530HW & NATL-560HW.  
Can be joined together to create custom lengths.

- NRA-6035W/6** - 6' Flexible Power Cord
- NRA-6035W/10** - 10' Flexible Power Cord



Used to convert NATL-530HW & NATL-560HW into a direct plug-in driver.


### NUSP-JBox - Junction Box for Hardwired LED Drivers



- A: Width:** 4-1/2"
- B: Length:** 2-3/4"
- C: Height:** 1-1/2"

To be used with NATL-530HW, NATL-560HW, or NATL-5100 Drivers.  
Capable of feeding two separate LED Drivers. Accepts Romex® or flex.  
Includes (1) male to male connector and (1) male to female connector. UL Listed.


- NALTL-10** - 10' Power Line Connector
- NALTL-30** - 30' Power Line Connector



Male connector lead to replace 10' power line connector  
included with NMT-60/24C2 & NMT-60/96C2.

# 24V RGB TAPE LIGHT CONTROLLER & LED DRIVERS


**NATL-524** - 24W Direct Plug-In Driver  
**NATL-545** - 45W Direct Plug-In Driver



A: Driver Width: 1-3/4"  
 B: Driver Length: 1-1/2"  
 C: Driver Height: 3-3/4"

Direct Plug-In Driver allows direct connection to the LED Tape Light.  
 Includes a 6' Power Line Connector Cable.


**NARGB-760** - RGB Controller



A: Width: 2"  
 B: Length: 4-3/4"  
 C: Height: 1"

RGB Controller is needed for each tape light run.  
 RGB Controllers can be synchronized to change simultaneously.  
 Capable of creating several colors or automated changing of visual spectrum.  
 Can be controlled locally or with Hand Held remote (NARGB-761).


**NATL-530HW** - 30W Class II Hardwired LED Driver  
**NATL-560HW** - 60W Class II Hardwired LED Driver



|                   | <b>NATL-530HW</b> | <b>NATL-560HW</b> |
|-------------------|-------------------|-------------------|
| A: Driver Width:  | 1-3/4"            | 2-3/8"            |
| B: Driver Length: | 5-5/8"            | 7"                |
| C: Driver Height: | 1-1/4"            | 1-3/8"            |

Hardwired LED Driver allows for driver to be hardwired with NUSP-JBox (required).  
 The power line connector is 3-1/4" long and the input wire is 4" long.  
 Can be converted into plug-in driver with NRA-6035W/6 or NRA-6035W/10.


**NARGB-761** - Hand Held Remote Control



A: Width: 1-7/8"  
 B: Length: 3-1/2"  
 C: Height: 1/4"

For remote control of RGB Controller up to 22' away (must be in direct view of controller)  
 Used to program RGB Tape Light run to certain color configurations.

**NATL-5100** - 100W Class II Plug-In LED Driver




A: Driver Width: 2-5/8"  
 B: Driver Length: 7-7/8"  
 C: Driver Height: 1-3/8"

Cord and Plug can be cut to be hardwired with NUSP-JBox.  
 The power line interconnector is 3-1/4" long and the cord and plug is 6'.

**NMT-60/24C2** - 60W Class II Magnetic Hardwire LED Driver  
**NMT-96/24C2** - 96W Class II Magnetic Hardwire LED Driver

NOTE: De-rate by 25% for maximum run.



A: Driver Width: 2-1/2"  
 B: Driver Length: 6-5/8"  
 C: Driver Height: 2-3/8"

Includes 10' power line connector (NALTL-10).  
 Manual reset thermal circuit-secondary side.  
 For a longer power line connector or additional, use NALTL-30.