

TRANSIT

Specifications:

Description:

Transit is a uniquely styled series with clean design flexibility. Can mount to ceiling or wall. One-light LED fixture with white acrylic diffuser. 3000K, 90+CRI 1,211 lumens.

Construction:

- Brushed Nickel (-09) (plated)
- White acrylic diffuserLED Module is replaceable (part # 93053641)
- Flicker-free dimming to 10% brightness with most ELV type dimmers
 (See Dimming Notes)
- Title 24 compliant
- Back plate covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- Six inches of wire supplied



Fixture Type: Location:

Contact:

Wall or ceiling mount .

PROGRESS

P3411-0930K9

Images:



Dimensions:

Square: 11"
Height: 3-3/4"
Depth: 3-3/4"
H/CTR: 5-1/5"

Performance:

Number of Modules	1
Input Power	17W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1211/71.2 (LM-79) per module
ССТ	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus
	ENERGY STAR [®] qualified

Catalog number:

Base	Finish	_ Color Temp	CRI
P3411	09 - Brushed Nickel	30K - 3000K	9 - 90 CRI



TRANSIT

Wall or ceiling mount •



P3411-0930K9

Dimming Notes:

P3411 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300P)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.