

FRESNEL LENS

Ceiling stem mount • Damp location listed



Specifications:

Description:

The Fresnel one-light LED mini-pendant has an antique-inspired Fresnel glass lens, industrial roots in form and function. 3000k, 90+ CRI 623 lumens.

Construction:

- Oil Rubbed Bronze (-108) (painted)
- Steel construction Clear Fresnel glass lens LED Module is replaceable (part # 93054049)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- Title 24 compliant
- Canopy covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- Ten feet of wire supplied

Performance:

Number of Modules	1
Input Power	9W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

P5050-10830K9

Images:



Dimensions:

Diameter: 6-1/8"
Height: 6-1/4"
Overall ht. w/stem: 72-1/4"

Catalog number:

Base	Finish	Color Temp	CRI
P5050	108 - Oil Rubbed Bronze	30K - 3000K	9 - 90 CRI

P5050-10830K9

Dimming Notes:

P5050 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300P)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.