

# BELL

Ceiling stem mounted • Wet location listed



## Specifications:

### Description:

The one-light hanging lantern from the Belle LED Collection features nautical undertones and a cage reminiscent of industrial spaces. Ideal for both interior and exterior settings. 3000K, 90+ CRI, 623 lumens. This fixture is also convertible to a ceiling mount fixture.

### Construction:

- Textured Graphite (-136) (powdercoat)
- Aluminum construction
- Glass: Etched glass diffuser
- LED Module is replaceable (Part # 93054049)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- CA Title 24 compliant
- Canopy covers a standard 4" hexagonal recessed outlet box
- 6 Links 9 gauge chain supplied
- Mounting strap for outlet box included
- 10 feet of wire supplied

### Performance:

Number of Modules	1
Input Power	9W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30
Max. Operating Temp	30
Warranty	5 year warranty
Labels	cCSAus Wet location listed ENERGY STAR® qualified

## P6536-13630K9

### Images:



### Dimensions:

Diameter: 6-5/8"  
 Height: 11-3/8"  
 Overall ht. w/stem: 77"

### Catalog number:

Base	Finish	Color Temp	CRI
P6536	136 - Textured Graphite	30K -3000K	9 - 90 CRI

**P6536-13630K9****Dimming Notes:**

---

P6536 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

**Electronic Low Voltage ELV Reverse Phase Controls**

---

Lutron	Diva Series	(Part Number DVELV-300P)
--------	-------------	--------------------------

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.  
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.