

Project:

Type:

Prepared By:

Date:



UPC: 019813834054



### Features and Benefits

Replacement for conventional decorative lamps

Filament LED construction gives a unique traditional look and feel for decorative and ambient applications

Rated for use in enclosed and open fixtures in dry and damp locations

Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs

ENERGY STAR Compliant, UL Listed

Smooth uniform dimming down to 10% (check dimmer compatibility list)

## Technical Specifications

### Performance

#### Product Type:

Decorative

#### Input Wattage:

4.3W

#### Lumens (Nominal):

450lm

#### Efficacy:

100 lm/W

#### Color Accuracy (CRI):

80 CRI

#### L70 Lifespan:

15,000 Hours

### Dimmable:

Yes

### Construction

#### Bulb Shape:

A15

#### Finish:

Frosted

#### Base Type:

E26

#### Beam Angle:

300°

#### For Use Outdoors in Open Fixtures:

Yes

### Other

#### Equivalency:

40W Incandescent

#### Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

### LED Characteristics

#### Color Temperature:

2700K Soft White

### Electrical

#### Power Factor:

0.7

#### Operating Temperature:

-20°C - 45°C

Technical Specifications (continued)

Electrical

Input Voltage:

120V

Operating Frequency:

60 Hz

Electrical Characteristics

Input Current @ 120V:

62mA

Compliance

UL Listed:

Yes

ENERGY STAR V2.0:

This product is ENERGY STAR® Version 2.0 Certified

Energy Star Model Number:

A10033

Energy Star ID:

2340545


CEC Status:

Not lawful for sale in California

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	6.3	4.3	8.5
PALLET	3600	44.9	46.5	40.2

Dimension



Light Distribution

