Project: Type: Prepared By: Date:



#### **Features and Benefits**

Energy efficient replacement for incandescent and halogen lamps

Constructed from durable plastic which lowers risk of breakage

Rated for use in enclosed and open fixtures in dry or damp locations (>15W A19 is Open fixture rated)

Frosted lens produces smooth diffuse light

Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs

**ENERGY STAR Compliant** 

Dimmable with common dimmer types (check compatibility list)

### **Technical Specifications**

**Performance** 

**Product Type:** 

A-Line

Input Wattage:

10W

**Typical Lumen Output:** 

800

Efficacy:

80 lm/W

**Color Temperature:** 

2700K Soft White

CRI:

80

L70 Lifespan:

15,000 Hours

**Dimmable:** 

Yes, down to 10%

Construction

**Bulb Shape:** 

A19

**Base Type:** 

E26

Beam Angle:

230°

For Use Outdoors in Open Fixtures:

No

Other

**Equivalency:** 

60W Incandescent

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

**Electrical** 

**Power Factor:** 

≥0.7

**Operating Temperature:** 

-20°C - 45°C

Input Voltage:

120V

## **Technical Specifications (continued)**

**Electrical** 

**Compliance** 

**Operating Frequency:** 

60 Hz

UL Listed: Yes

Electrical Characteristics ENERGY STAR V2.0:

Input Current @ 120V: This product is ENERGY STAR® Version 2.0 Certified

101mA

**Energy Star ID:** 

2357502

**CEC Status:** 

Not lawful for sale in California

### **Case and Pallet Dimensions**

|        | QTY  | LENGTH (in) | WIDTH (in) | HEIGHT (in) |
|--------|------|-------------|------------|-------------|
| CASE   | 12   | 15.4        | 5.2        | 4.9         |
| PALLET | 2268 | 47.2        | 39.4       | 45.7        |

# **Dimension**



