

Project: Type: Prepared By: Date:



#### **Features and Benefits**

Replacement for traditional Metal Halide or High Pressure Sodium HID Lamps

Ideal for wall pack retrofit applications

Optimized for Horizontal Applications with Directional Light Output and Rotatable base

Active Cooling: Internal sensor overheat and engaged will automatically reduce output to 70% rated wattage until the sensor cools and will light up again to 100%

Integral Driver enables lamp to be wired directly to line voltage without need for an external driver or ballast

Rated for use in enclosed and open fixtures in dry or damp locations

4kV surge protection built in

50,000 hour Lifespan

Environmentally friendly, no mercury used

UL Listed, UL Classified, DLC Listed

Non-Dimmable

5 Year No Compromise Warranty

## **Technical Specifications**

**Performance** 

**Product Type:** 

HID Replacement

Input Wattage:

60W

**Typical Lumen Output:** 

9300

Efficacy:

155 lm/W

**Color Temperature:** 

4000K Cool White

CRI:

80

L70 Lifespan:

50,000 Hours

**Dimmable:** 

No

Construction

**Bulb Shape:** 

Wall Pack

**Base Type:** 

EX39

**Beam Angle:** 

180°

Other

**Equivalency:** 

250W HID

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

**Electrical** 

**Power Factor:** 

0.9

Operating Temperature:

-30°C - 60°C

Input Voltage:

100-277V

**Operating Frequency:** 

50/60Hz



# **Technical Specifications (continued)**

Installation

THD

**Installation Type:** 

<20%

Type B, Ballast Bypass

Compliance

Installation Orientation:

**UL Listed:** 

Universal Installation

Yes

**Technical Specifications** 

**UL Classified:** 

For Use Outdoors in Open Fixtures:

Yes

Yes

**DLC Model Number:** 

**Electrical Characteristics** 

HID-60-H-EX39-840-BYP-WP

Flicker:

<30%

## **Minimum Compartment Size**

Length x Width x Height [in]	Lamp Quantity
7.9 x 7.9 x 11.8	1

### **Case and Pallet Dimensions**

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	16.7	12.7	12.6
PALLET	216	27.3	35.4	42.5

# CEC Status:

Lawful for sale in California

#### **DLC Listed:**

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. DLC Product Code: PJT9AXRP





