

Products

- > [Index](#)
- > [Featured Products](#)
- > [Cross Reference](#)
- > [UPC Search](#)

**Product Datasheet**

[Catalog Home](#) [Home Page](#)

[Search](#)

## 1554 -- Combination Coupling 1" Rigid / IMC to 1" Flex



**Product Specifications**

<b>Family</b>	Flexible Metal Conduit Fittings & Rigid and IMC Fittings
<b>Fittings Classification</b>	Combination Couplings
<b>Sub Class</b>	Squeeze Threaded
<b>Trade Size</b>	1"
<b>Standard Packaging</b>	Carton
<b>Ship Carton Length</b>	8.25
<b>Ship Carton Width</b>	6.00
<b>Ship Carton Height</b>	5.5
<b>WT. PER HU.</b>	34
<b>Dimension A</b>	2-3/16"
<b>Dimension B</b>	1-1/2"
<b>Dimension C</b>	1-7/32"
<b>Thread Spec. D</b>	1-11-1/2 - 1-1/2 NPT
<b>Dimension E</b>	1-13/16"
<b>Unit Carton Quantity</b>	25
<b>Ship Carton Quantity</b>	25
<b>UPC Number</b>	050169015544
<b>Product UPC-A Labeled</b>	No
<b>Catalog PDF Page</b>	<a href="#">PDF Catalog Page</a>

### Applications

- Use RACO® Cat. Nos. 1552-1554 when coupling flexible metal conduit to threaded rigid/IMC

### Product Features

- All malleable construction insures mechanical protection
- All components are zinc electro plated for corrosion protection

### Compliances

C/UL/US

