




AC CABLE 90 DEGREE SQUEEZE TYPE

90° Squeeze Connectors, Uninsulated Throat Malleable Iron
N/A

B69



Catalog #: 2201

APPLICATIONS

- For use in dry locations to bond flexible metal conduit to a box or enclosure
- N/A
- For use in dry locations to bond armored cable to a box or enclosure

PRODUCT FEATURES

- All malleable iron construction insures mechanical protection for the raceway
- Electro zinc plated for added corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation

CULUS

UL Listed E195969

GENERAL PRODUCT INFORMATION

Sub Class: Uninsulated
 Trade Size: 3/8 in.

DRAWING DIMENSIONS

Dimension A: 2-1/64 in.
 Dimension B: 23/64 in.
 Thread Spec. B: 1/2 in. - 14 NPS
 Dimension C: .570 in.
 Dimension D: .390-.630 in.
 Dimension E: 1-3/8 in.

PACKAGING

Package Type: Carton
 Ship Carton Qty.: 50
 Product UPC-A Labeled: No
 Weight (Lbs. Per/C): 8.70
 Ship Carton Length (in.): 10.00
 Ship Carton Width (in.): 5.25
 Ship Carton Height (in.): 4.31
 Ctn Weight (Lbs.): 7.95
 UPC Number: 050169022016
 I2of5: 50050169022011