

Products

- › [Index](#)
- › [Featured Products](#)
- › [Cross Reference](#)
- › [UPC Search](#)

Product Datasheet

[Catalog Home](#) [Home Page](#)

[Search](#)

2800 -- Metal Clad Cable Connector 1/2"



Product Specifications

Family	Metal Clad Cable Connectors
Fittings Classification	Steel - Snap In Connectors
Sub Class	for MCI A/C and HCF Cables
Trade Size	1/2"
Cable Range	MCI: .410-.610 AL&ST; MCI-A: .500-.610; AC: 10/3 - .470-.630 ST; 10/2 - .480-.580 AL
Standard Packaging	Carton
Ship Carton Length	1.46875
Ship Carton Width	.59375
Ship Carton Height	1.5625
WT. PER HU.	8.1
Unit Carton Quantity	50
Ship Carton Quantity	50
UPC Number	050169028001
Catalog PDF Page	PDF Catalog Page

Applications

- For use in dry locations to connect MCI, AC and HCF cable to a box or enclosure
- For use in dry locations to connect MCI-A cable .500" - .610" in diameter to a box or enclosure

Product Features

- Easy to install, just tilt, insert and snap down
- Tri-head screw/clamp design -- connector can be installed by using a slotted, Phillips or Robertson head screwdriver
- Integral insuliner -- provides for maximum wire protection
- Durable all-steel construction
- Zinc electroplated -- for corrosion protection
- RACO MCI, AC and HCF connectors are suitable for applications up to 600 V

Compliances

cULus

REDI-LOC® SELECTION GUIDE		
CABLE TYPE	2800 1/2" KO	2801 3/4" KO
AC Steel	14/2, 14/3, 14/4, 12/2, 12/3, 12/4, 10/2, 10/3	10/4, 10/5, 8/3, 8/4, 6/3
HCF Steel	14/2, 14/3, 12/2, 12/3, 10/2	—
AC Aluminum	14/2, 14/3, 14/4, 12/2, 12/3, 12/4	10/4, 8/3, 8/4
MCI Steel	14/2, 14/3, 14/4, 12/2, 12/3, 12/4, 10/2	10/3, 10/4, 8/2, 8/3
MCI Aluminum	14/2, 14/3, 14/4, 12/2, 12/3, 12/4, 10/2	10/3, 10/4, 8/2
MCI Aluminum	14/3, 14/4, 12/2, 12/3, 12/4, 10/2, 10/3	—