


**FLEXIBLE METAL 90 DEGREE SQUEEZE CONNECTORS****90° Squeeze Connectors Malleable Iron****B63**

Catalog #: 3203

APPLICATIONS

For use in dry locations to bond flexible metal conduit to a box or enclosure
For use in dry locations to bond armored cable to a box or enclosure

PRODUCT FEATURES

All malleable iron construction insures mechanical protection for the raceway
Electro zinc plated for added corrosion protection
UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation
N/A

CULUS

UL Listed E195969

COMPLIANCES

MSDS
[www.hubbell-rtb.com/certifications/Hubbell-RACO MSDS for WP Boxes and Fittings, January 2015.pdf](http://www.hubbell-rtb.com/certifications/Hubbell-RACO%20MSDS%20for%20WP%20Boxes%20and%20Fittings,%20January%202015.pdf)

GENERAL PRODUCT INFORMATION

Sub Class: Insulated
Trade Size: 3/4 in.

DRAWING DIMENSIONS

Dimension A: 2-1/2 in.
Dimension B: 1/2 in.
Thread Spec. B: 3/4 in. - 14 NPS
Dimension C: .822 in.
Dimension D: .830-1.110 in.
Dimension E: 1-31/32 in.

PACKAGING

Package Type: Carton
Ship Carton Qty.: 25
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 17.90
Ship Carton Length (in.): 10.00
Ship Carton Width (in.): 5.25
Ship Carton Height (in.): 4.31
Ctn Weight (Lbs.): 4.48
UPC Number: 050169032039
I2of5: 50050169032034