

Products

- › Index
- › Featured Products
- › Cross Reference
- › UPC Search

**Product Datasheet**

[Catalog Home](#) [Home Page](#)

[Search](#)

## 3308DB -- Double Bite Saddle Connector Straight 2" Trade Size Insulated



**Product Specifications**

<b>Family</b>	Double Bite Saddle Connector
<b>Fittings Classification</b>	Double Bite Saddle Connector
<b>Sub Class</b>	Insulated
<b>Trade Size</b>	2"
<b>Standard Packaging</b>	Carton
<b>Ship Carton Length</b>	3.9
<b>Ship Carton Width</b>	3.7
<b>Ship Carton Height</b>	3.5
<b>WT. PER HU.</b>	87.0
<b>Dimension A</b>	2-9/16"
<b>Dimension B</b>	3"
<b>Dimension C</b>	5/8"
<b>Unit Carton Quantity</b>	1
<b>Ship Carton Quantity</b>	1
<b>UPC Number</b>	050169533086
<b>Inner Leaf 2 of 5 Bar Code</b>	50050169533081

**Applications**

- Use RACO DOUBLE BITE saddle connectors in dry locations to connect flexible metal conduit, MCI, MCI-A and AC cable to a box or enclosure

**Product Features**

- Straight connectors have all steel construction that ensures mechanical protections for raceways
- The straight connectors are available in 3/8" to 4" trade sizes
- 90° connectors have malleable iron & steel construction for added strength
- 90° connectors are available in 3/8" to 1" trade sizes
- Dual saddle clamp ensures proper conduit and cable connection for raceway
- Zinc plated for corrosion resistant installation

- Tri-head screw/clamp design - connectors can be installed by using a slotted, Phillips or Robertson head screwdriver
- Insulated throats for all DOUBLE BITE provides for maximum wire protection
- RACO DOUBLE BITE saddle connectors comply with UL standard 514B and NEMA FB-1. No need to worry about code compliances

**Compliances**

**C / UL / US**