

Products

- › [Index](#)
- › [Featured Products](#)
- › [Cross Reference](#)
- › [UPC Search](#)

**Product Datasheet**

[Catalog Home](#) [Home Page](#)

[Search](#)

## 3512-3 -- 1/2" Trade Size Straight Liquidtight with #14 - #4 Grounding Lug



**Product Specifications**

<b>Family</b>	Liquidtight Conduit and Cord Connectors
<b>Fittings Classification</b>	Grounding Liquidtight Connectors
<b>Sub Class</b>	Insulated
<b>Trade Size</b>	1/2"
<b>Standard Packaging</b>	Carton
<b>Ship Carton Length</b>	8.25
<b>Ship Carton Width</b>	5.00
<b>Ship Carton Height</b>	4.00
<b>WT. PER HU.</b>	21.8
<b>Dimension A</b>	1-3/16"
<b>Dimension B</b>	1/2"
<b>Thread Spec. B</b>	1/2-14 NPT
<b>Dimension C</b>	1-15/32"
<b>Dimension D</b>	25/32"
<b>Unit Carton Quantity</b>	25
<b>Ship Carton Quantity</b>	25
<b>UPC Number</b>	050169351239

**Applications**

- For use in outdoor or indoor locations on flexible metallic

liquidtight conduit, when installation of a copper or aluminum external bonding jumper is required

- RACO® grounding liquidtight connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

#### Product Features

- Patented split gland-ring is designed to slip onto the conduit quickly and to grip the jacket of the conduit, speeding installation, assuring a perfect seal, and preventing pullouts
- All components are reusable -- RACO® liquidtight connectors may be easily disassembled and reused after years of service
- Sealing washer (included) provides a liquidtight seal when terminating the connector in a threadless opening
- Heavy duty locknut included with every RACO® liquidtight connector assures continuity of ground
- All metallic components are zinc electro plated for added corrosion protection
- Bodies - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron ; •Nuts - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron

#### Compliances

UL CSA

