

Products

- › [Index](#)
- › [Featured Products](#)
- › [Cross Reference](#)
- › [UPC Search](#)

Product Datasheet

[Catalog Home](#)[Home Page](#)[Search](#)

3513-3 -- 3/4" Trade Size Straight Liquidtight with #14 - #4 Grounding Lug



Product Specifications

Family	Liquidtight Conduit and Cord Connectors
Fittings Classification	Grounding Liquidtight Connectors
Sub Class	Insulated
Trade Size	3/4"
Standard Packaging	Carton
Ship Carton Length	10.00
Ship Carton Width	5.25
Ship Carton Height	4.3125
WT. PER HU.	24.9
Dimension A	1-13/32"
Dimension B	9/16"
Thread Spec. B	3/4-14 NPT
Dimension C	1-31/64"
Dimension D	25/32"
Unit Carton Quantity	25
Ship Carton Quantity	25
UPC Number	050169351338

Applications

- For use in outdoor or indoor locations on flexible metallic

liquidtight conduit, when installation of a copper or aluminum external bonding jumper is required

- RACO® grounding liquidtight connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

Product Features

- Patented split gland-ring is designed to slip onto the conduit quickly and to grip the jacket of the conduit, speeding installation, assuring a perfect seal, and preventing pullouts
- All components are reusable -- RACO® liquidtight connectors may be easily disassembled and reused after years of service
- Sealing washer (included) provides a liquidtight seal when terminating the connector in a threadless opening
- Heavy duty locknut included with every RACO® liquidtight connector assures continuity of ground
- All metallic components are zinc electro plated for added corrosion protection
- Bodies - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron ; •Nuts - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron

Compliances

UL CSA

