

Products

- › Index
- › Featured Products
- › Cross Reference
- › UPC Search

**Product Datasheet**

[Catalog Home](#) [Home Page](#)

[Search](#)

## 3518-3 -- Straight Liquidtight with #14 - #4 Grounding Lug 2"



**Product Specifications**

|                                |   |
|--------------------------------|---|
| <b>Family</b>                  | Liquidtight Conduit and Cord Connectors |
| <b>Fittings Classification</b> | Grounding Liquidtight Connectors        |
| <b>Sub Class</b>               | Insulated                               |
| <b>Trade Size</b>              | 2"                                      |
| <b>Standard Packaging</b>      | Carton                                  |
| <b>Ship Carton Length</b>      | 9.1875                                  |
| <b>Ship Carton Width</b>       | 6.25                                    |
| <b>Ship Carton Height</b>      | 5.0625                                  |
| <b>WT. PER HU.</b>             | 126.7                                   |
| <b>Dimension A</b>             | 3-1/32"                                 |
| <b>Dimension B</b>             | 21/32"                                  |
| <b>Thread Spec. B</b>          | 2-11-1/2 NPT                            |
| <b>Dimension C</b>             | 2-9/32"                                 |
| <b>Dimension D</b>             | 25/32"                                  |
| <b>Unit Carton Quantity</b>    | 5                                       |
| <b>Ship Carton Quantity</b>    | 5                                       |
| <b>UPC Number</b>              | 050169351833                            |

**Applications**

- For use in outdoor or indoor locations on flexible metallic

liquidtight conduit, when installation of a copper or aluminum external bonding jumper is required

- RACO® grounding liquidtight connectors are suitable for use in Class 1, Division 2; Class 2, Division 1 and 2; and Class 3, Division 1 and 2 hazardous locations

#### Product Features

- Patented split gland-ring is designed to slip onto the conduit quickly and to grip the jacket of the conduit, speeding installation, assuring a perfect seal, and preventing pullouts
- All components are reusable -- RACO® liquidtight connectors may be easily disassembled and reused after years of service
- Sealing washer (included) provides a liquidtight seal when terminating the connector in a threadless opening
- Heavy duty locknut included with every RACO® liquidtight connector assures continuity of ground
- All metallic components are zinc electro plated for added corrosion protection
- Bodies - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron ; •Nuts - 3/8" to 1" Steel ; 1-1/4" to 4" Malleable Iron

#### Compliances

UL CSA

