

shat-r-shield[®] INC.

090HY50STCLVLN000001

90W STDRD MNT, CLEAR LENS, 120-277V



Ambient Temp. Range: -30+45 C

Average Life Hours: 60000

Color: Black

Construction: Thermal Polymer

Dimmable: Yes

Filament Type: LED

Fixture Watts: 90.0

Height: 5.60 IN

Length: 10.25 IN

Lumens: 10700

Number of Lamps: 1

Package Weight: 10.20 L

Pack By: 1

Size (LxWxH): 10.25 IN x 13.00 IN x 5.60 IN

Type: 90W Standard Mount, Clear Lens

Voltage: 120-277 V

Width: 13.00 IN

Application: Washdown, Food Processing, Marine Areas

Driver Type: LED Driver

Color Temperature: 5000 K

CRI: 70

Enclosure: Thermal Polymer Housing

Fixture Type: 90W Standard Mount, Clear Lens

Frequency Rate: 50/60

Lamp Type: LED

Material: Thermal Polymer Housing

Mounting: Standard

Package (LxWxH): 15.50 IN x 15.50 IN x 10.00 IN

Power Factor: 0.9

Power Source: LED Driver

Style: 90W LED Standard Mount

UPC: 726585394968

Wattage: 90.0 W

IP60K HIGH TEMP JETS HIGH PRESSURE	IP66 WATERPROOF DUST TIGHT	NEMA 4x WATERTIGHT	NEMA 5 DUST-TIGHT
UL 1598 LUMINAIRE	UL 1598A MARINE GRADE	UL WET LOCATION	USDA APPROVED

