

Product Number: 49419

Order Abbreviation: QS2X54T5HOUNVPS80SC

General Description: 2-lamp Universal Voltage bi-level electronic ballast for 54W T5HO lamp with integral lead wires, packaged 10 pieces per case



Product Information

Abbrev. With Packaging Info.	QS2X54T5HOUNVPS80SC 10/CS 1/SKU
Ballast Factor	0.4
Ballast Height H (in)	1.1810
Ballast Length L (in)	9.4690
Ballast Width W (in)	1.6300
Circuit Type	Series
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Power Factor	>0.98
Primary Lamp Type	FP54T5HO
Sound Rating	A
Starting Method	PROStart
Starting Temperature - Fahrenheit	50
Starting Temperature - Celsius	10
Total Harmonic Distortion (THD)	<10%
Wiring Method	Leads



QUICK60+SM
277V 60/60Hz

QUICKSENSESM

PROStartTM
PROGRAMMABLE START

Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 10 feet
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Ground ballast case
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Input Frequency: 50/60Hz.
- Minimum Starting Temperature: 32F/0C.