



Product Number: 49674

Order Abbreviation: QT2X54/277PHO-DIM

General Description: 2-lamp 277V dimming electronic ballast for 54W T5 HO lamp, DL and Circline lamps

Product Information

Abbrev. With Packaging Info.	QT2X54277PHODIM 277V 20/CS 1/SKU
Ballast Factor	1.00
Ballast Height H (in)	1.1800
Ballast Length L (in)	16.7300
Ballast Width W (in)	1.1800
Circuit Type	SERIES
Family Brand Name	QUICKTRONIC
Input Current (Amps)	0.00
Nominal Voltage (V)	277V
Number of Lamps	2
Power Factor	>0.97
Primary Lamp Type	FP54T5HO
Sound Rating	A
Starting Method	PROGRAMMED START
Starting Temperature - Fahrenheit	50
Starting Temperature - Celsius	10
Total Harmonic Distortion (THD)	<10%
Wiring Method	WIRETRAP CONNECTORS



QUICK60+™
SYSTEM WARRANTY

QUICKSENSE™

PRO Start™
PROGRAMMED START

Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 7 feet
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Ground ballast case
- Install in accordance with National Electric Codes
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Input Frequency: 60Hz.
- Minimum Starting Temperature: 50F/10C.

- Data shown is at full light output.