

2900HA Series Electric Baseboard - High Altitude Convection Heater



Features

- Available in white or ivory with Aluminum heating element and Aluminum fins.
- Painted 22 gauge steel front with 20 gauge junction boxes located on each end of the heater - junction boxes contain quick connect cable clamps and 6" ground lead wires.
- Over-temperature thermal limit extends entire length of heated area.
- A full length wireway provided along the back of the heater.
- Optional enclosed conduit wireway available.
- Heater can be mounted to the wall by using the key hole knockouts every 4" at the back of the heater.
- Optional In-Built thermostats field installed in the junction box.
- Ivory available with extended lead times, consult factory.
- Made in U.S.A. • Height: 6" Depth: 2 1/2"

Standard Models

WHITE		WATTS	BTUs	VOLTS	AMPS	HEATER LENGTH (IN)	WT. (LBS)
MFG CATALOG NUMBER	MFG MODEL NUMBER						
01012202	E2903-024HAW	375	1275	120	3.1	24	5
01012302	F2903-024HAW	375	1275	208	1.8		
01012402	H2903-024HAW	375 / 281	1275 / 955	240 / 208	1.6/1.4		
01012502	G2903-024HAW	375 / 281	1275 / 955	277 / 240	1.6/1.2	28	6
01012602	E2905-028HAW	500	1706	120	4.2		
01012702	F2905-028HAW	500	1706	208	2.4		
01012802	H2905-028HAW	500 / 375	1706 / 1275	240 / 208	2.1/1.8	36	7
01012902	G2905-028HAW	500 / 375	1706 / 1275	277 / 240	1.8/1.6		
01013002	E2906-036HAW	600	2040	120	5		
01013102	F2906-036HAW	600	2040	208	2.9	40	8
01013202	H2906-036HAW	600 / 450	2040 / 1530	240 / 208	2.5/2.2		
01013302	G2906-036HAW	600 / 450	2040 / 1530	277 / 240	2.2/1.9		
01013402	E2907-040HAW	750	2550	120	6.3	48	10
01013502	F2907-040HAW	750	2550	208	3.6		
01013602	H2907-040HAW	750 / 563	2550 / 1914	240 / 208	3.1/2.7		
01013702	G2907-040HAW	750 / 563	2550 / 1914	277 / 240	2.7/2.6	60	12
01013802	E2910-048HAW	1000	3413	120	8.3		
01013902	F2910-048HAW	1000	3413	208	4.8		
01014002	H2910-048HAW	1000 / 750	3413 / 2550	240 / 208	4.2/3.6	72	14
01014102	G2910-048HAW	1000 / 750	3413 / 2550	277 / 240	3.6/3.1		
01014202	G2907-048HAW	750	2550	277	3.4		
01014302	E2912-060HAW	1250	4250	120	10.4	96	18
01014402	F2912-060HAW	1250	4250	208	6		
01014502	H2912-060HAW	1250 / 938	4250 / 3189	240 / 208	5.2/4.5		
01014602	G2912-060HAW	1250 / 938	4250 / 3189	277 / 240	4.5/3.9	120	22
01014702	G2909-060HAW	938	3189	277	3.4		
01014802	E2915-072HAW	1500	5100	120	12.5		
01014902	F2915-072HAW	1500	5100	208	7.2	18	31
01015002	H2915-072HAW	1500 / 1125	5100 / 3825	240 / 208	6.3/4.7		
01015102	G2915-072HAW	1500 / 1125	5100 / 3825	277 / 240	5.4/4.7		
01015202	G2911-072HAW	1125	3825	277	4.1	10	10
01015702	F2920-096HAW	2000	6826	208	9.6		
01015802	H2920-096HAW	2000 / 1500	6826 / 5100	240 / 208	8.3/7.2		
01015902	G2920-096HAW	2000 / 1500	6826 / 5100	277 / 240	7.2/6.3	11	11
01016002	G2915-096HAW	1500	5100	277	5.4		
01016502	F2925-120HAW	2500	8532	208	12		
01016602	H2925-120HAW	2500 / 1875	8532 / 6375	240 / 208	10.4/9.0	13	13
01016702	G2925-120HAW	2500 / 1875	8532 / 6375	277 / 240	9.0/7.8		
01016802	G2918-120HAW	1875	6375	277	6.8		

2900A Series - International Models

WHITE		WATTS	BTUs	VOLTS	HEATER LENGTH (IN)	WT. (LBS)
MFG CATALOG NUMBER	MFG MODEL NUMBER					
01157602	M2903-24AWi	375	1275	220	24"	10
01157702	H2903-24AWi			240		
01157802	M2905-28AWi	500	1706	220	28"	11
01159702	H2905-28AWi			240		
01158002	M2906-36AWi	600	2040	220	36"	11.5
01158102	H2906-36AWi			240		
01158202	M2907-40AWi	750	2550	220	40"	13
01158302	H2907-40AWi			240		
01158402	M2910-48AWi	1000	3413	220	48"	14
01158502	H2910-48AWi			240		
01158602	M2912-60AWi	1250	4250	220	60"	16
01158702	H2912-60AWi			240		
01158802	M2915-72AWi	1500	5100	220	72"	19
01158902	H2915-72AWi			240		
01159002	M2917-84AWi	1750	5950	220	80"	22
01180002	H2917-84AWi			240		
01180302	M2925-120AWi	2500	8532	220	120"	31
01180402	H2920-120AWi			240		

Note: Wireway length is the same as baseboard length.