


RIGID BODIES AND ASSEMBLIES

LL Assembly N/A

C13





Catalog #: RLL300

APPLICATIONS

For use with threaded rigid/IMC conduit for pulling access or to split a run into multiple directions. Removable cover allows access for maintenance and making taps and splices to conductors.

N/A

PRODUCT FEATURES

Durable die cast aluminum construction Premium powder coat finish Includes NBR synthetic rubber gasket Stamped aluminum cover Combination head screw

UL LISTED

File E331564

NEMA

NEMA 3R rated

NEC

2014 NEC® compliant

GENERAL PRODUCT INFORMATION

Trade Size: 3 in.

DRAWING DIMENSIONS

Dimension A: 12.83 in. 5.89 in. 4.53 in. Dimension B: Dimension C: 4.49 in. 11.250 in. Dimension D: Dimension E:

Tapped holes #5/16UNC-2B 3-8NPT Dimension F:

30092326213296

Dimension G: Dimension H: 3.058 in.

PRODUCT MEASUREMENTS

179.8 (2946.4) Cubic Inches (cm3):

PACKAGING

12of5:

Package Type:
Ship Carton Qty.:
Product UPC-A Labeled:
Weight (Lbs. Per/C): Carton Yes 430.00 Ship Carton Length (in.): 14.00 5.88 7.13 Ship Carton Width (in.): Ship Carton Height (in.): Ctn Weight (Lbs.): UPC Number: 4.30 092326213295