



Friendly Service ... Powerful Solutions™


Topaz Specification Sheet

Description: Rigid Conduit Couplings

Standard Material: Galvanized Steel / NPSM Thread Type

Features: "1/2 -4" Rigid Elbows meet UL 6 and ANSI C80.1
Federal Specification WW-C-563

Application: Indoors or Outdoors. Use to join threaded Rigid or IMC conduit together.



E223147

TOPAZ CAT#	A	B
51	1.63	1.563
52	1.64	1.625
53	1.97	2.000
54	2.03	2.063
55	2.06	2.063
56	2.13	2.125
57	2.19	3.125
58	3.31	3.250
59	3.41	3.375
60	3.52	3.500
60A	3.95	3.750
60B	4.25	4.000

TOPAZ CAT #	UPC#	SIZE	THREADS PER INCH	UNIT CTN	SHIP CASE	WT/ EACH
51	10130	1/2"	14	—	100	.12
52	10140	3/4"	14	—	50	.17
53	10150	1"	11 1/2	—	30	.29
54	10160	1 1/4"	11 1/2	—	25	.38
55	10170	1 1/2"	11 1/2	—	25	.53
56	10180	2"	11 1/2	—	20	.70
57	10190	2 1/2"	8	—	12	1.80
58	10200	3"	8	—	8	2.26
59	10210	3 1/2"	8	—	4	3.50
60	10220	4"	8	—	4	3.13
60A	10230	5"	8	—	2	4.75
60B	10240	6"	8	—	1	7.65

Approved by Topaz Quality Control & Engineering



NEW YORK
925 Waverly Avenue
Holtsville, NY 11742
800-666-2852
Fax: 800-333-3488

CALIFORNIA
225 Parkside Drive
San Fernando, CA 91340
888-551-2852
Fax: 888-690-2852

FLORIDA
2020 West 26th Street
Jacksonville, FL 32209
800-666-2852
Fax: 800-333-3488