




Stamped Bonding Plate – LPC540



- Stamped bonding plate suitable for structural steel applications
- Listed to UL® 96



Part Number	LPC540
Conductor Size, UL	Class 1 - Class 2 (4/0 Max)
Material	Copper
Finish	Bare
Contact Area	8 in ² Min
Depth [D]	2 1/8"
Height [H]	1 1/4"
Width [W]	4 1/4"
Hole Size 1 [HS1]	0.2"
Hole Size 2 [HS2]	0.311"
Unit Weight	0.56 lb
Certifications	UL
Standard Packaging Quantity	1 pc
UPC	78285642993

Stainless steel separator included with LPC540A for bi-metallic applications.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.