


# Service Entrance Suppressor, 200 kA with Metal Enclosure – SES200277480CM



- 200kA 8/20 $\mu$ s primary protection rated for service entrance applications
- Internal high interrupt capacity fusing for added safety
- Modular design allows easy replacement of surge modules
- Built-in disconnect and fusing eliminates need for external fusing
- Transient Discriminating (TD) Technology provides increased service life
- Includes surge counter and filtering



Part Number	SES200277480CM
Nominal System Voltage (Un)	277/480 V
Distribution System	3Ph Y 4W+G
Max Continuous Operating Voltage (Uc)	400/692 VAC
Stand-off Voltage	480/831 V
Frequency	50 – 60 Hz
Short Circuit Current Rating (SCCR)	200 kA
Nominal Discharge Current (In)	80 kA 8/20 $\mu$ s
Max Discharge Current (Imax)	100 kA 8/20 $\mu$ s
Impulse Current (Iimp)	20 kA 10/350 $\mu$ s
Voltage Protection Rating (VPR)	900.0 V @ 3 kA L-N 1,000.0 V @ 20 kA L-N
Aggregate Surge Rating	200 kA 8/20 $\mu$ s
Filtering	-40 dB @ 100 kHz
Max Operating Current	25 mA
Protection Modes	All modes protected
Status Indication	5 segment LED bar graph per phase Surge counter
Lead Size	#12 – #2
Temperature	14 – 140 °F
Enclosure Material	Metal
Enclosure Rating	NEMA®-4
Mounting	Wall mount

Part Number	SES200277480CM
Depth	7 1/2"
Height	16"
Width	14"
Unit Weight	28.66 lb
Certification Details	UL® 1449 Edition 3 Type 1/2, 20 kA Mode
Complies With	ANSI®/IEEE® C62.41.2-2002 Cat A, Cat B, Cat C ANSI®/IEEE® C62.41.2-2002 Scenario II, Exposure 3, 100 kA 8/20 µs, 10 kA 10/350 µs
Certifications	NOM
Standard Packaging Quantity	1 pc
UPC	78285667060
EAN-13	0782856667223

ANSI is a registered trademark of American National Standards Institute. IEEE is a registered trademark of The Institute of Electrical and Electronics Engineers, Inc. NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

**WARNING**

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.